

L'OLIO 100%


SOLVENT FREE HARDWAX OIL FOR WOODEN FLOORS

L'Olio 100% is a ready to use blend of natural oils and hard waxes suitable for finishing treatment of parquet and wood in internal. It can be used both on site or in an industrial process.

The product is solvent free but remains easy to apply. The oiled surface reaches a very good mechanical resistance with a single coat.

Particularly recommended in Green Building industry.

Available in neutral version and 27 standard colors (see color chart).



Technical data

Physical characteristics (20°C – 60% R.H)

Aspect	Dense liquid	Specific gravity	0,950 - 0,990 g/cm ³
--------	--------------	------------------	---------------------------------

Ratio & times (20°C – 60% R.H)

Polishing after application	within 15'-20'	Polishing	24 hours
Touch dry	8 hours		

Technical characteristics

Consumption (oil-spreader or brush)	~ 35 m ² /lt	Application temperature	> + 10°C
Consumption (spatula)	~ 50 m ² /lt		

Storage & Labeling

Storage in original closed packing at ambient temperature	12 months	Symbols of risk	None
		VOC content	< 50 g/lt

Tools cleaning	Immediately after use with Diluente RMD/91 or Green Cleaner		
-----------------------	---	--	--

Packaging	1 lt	2,5 lt
------------------	------	--------

Application

Support preparation

The wood surface to be treated must be dry and free from residues of previous treatments. Proceed with the sanding of the floor and if necessary use a filler for cracks and fissures (Idrostucco RS30). The last abrasive paper to be used must be 100 in order to improve the impregnation of the oil. Accurately clean the floor.

To get a more intense color and a softer touch it is recommended to sweep the surface with a well wrung cloth and then once dry, to sand with a buffing machine with a net (grid 100-120).

Application

- Mix L'Olio 100% before use
- Apply L'Olio 100% with a brush, a spatula or an oil-spreader
- Uniformly spread the product within 15-20 minutes with a buffing machine using a green pad at low speed (150 rpm) in order to remove the excess.
- Polish with a white pad after 24 hours (when the oil is perfectly dry).

Protection treatment

When the surface is perfectly dry, apply two coats of the water-proofing agent I.R.O. to improve the resistance to dirt and spots.

See major information on proper technical data sheet.



TOVER S.R.L.
Via Rosa Luxembourg 2/A
10093 COLLEGNO (TO)
P.IVA 07783540011
R.E.A. n°920259
Tel.: +39-011/7792823
Fax: +39-011/7792749
www.tover.com
e-mail: info@tover.com
Made in Italy





TOVER S.R.L.
 Via Rosa Luxembourg 2/A
 10093 COLLEGNO (TO)
 P.IVA 07783540011
 R.E.A. n°920259
 Tel.: +39-011/7792823
 Fax: +39-011/7792749
 www.tover.com
 e-mail: info@tover.com
 Made in Italy



Maintenance

An oiled surface absolutely needs a periodical maintenance to keep its original aspect; it is also very important that the first one must not be done before 20 days after the application. During this period of time it is better to avoid that water remains for a while on the floor.

A correct maintenance means a frequent cleaning with a neutral soap (Deteroil) and a periodical refreshing of the worn surface with a polish (Lux).

Small repairs

In order to repair small worn or damaged areas, use newly L'Olio 100% in the following way: wash the floor with Deteroil and let it dry for a few hours. Apply a small quantity of L'Olio 100% on the area spreading immediately with a soft cloth to leave only a very thin coat. After complete drying (24 hours) polish the area with a dry soft cloth.

Notes

- ✓ Do not apply L'Olio 100% on lacquers, nitro sealers or others but only on a perfectly sanded wood
- ✓ Mix well before use
- ✓ A high content of relative humidity, low temperature or species of woods like softwoods could slow down the oil drying time
- ✓ It is recommended to test the final effect of the treatment on a small area if the colored version is applied
- ✓ A cross-linker agent (Oil-Linker) can be added to L'Olio 100% as a B component in order to highly improve its resistance to water spots without worsening the application easiness.

Color Chart L'Olio 100%

The following table is purely indicative. The final result can change according to the wood species, its preparation, the application method and ambient conditions.

Always proceed to application tests.

 Cherry	 Teak	 Mahogany	 Walnut	 Antique Walnut	 Dark Walnut
 Wengé	 Black Ebony	 Neutral	 White	 Artic	 Smoke
 Whisky	 Pearl	 Rose	 Rose Grey	 Light Grey	 Grey
 Stone	 Fumé	 Tobacco	 Cappuccino	 Honey	 Lilla
 Green	 Moss	 Blue Capri	 Night Blue		



TOVER S.R.L.
Via Rosa Luxembourg 2/A
10093 COLLEGNO (TO)
P.IVA 07783540011
R.E.A. n°920259
Tel.: +39-011/7792823
Fax: +39-011/7792749
www.tover.com
e-mail: info@tover.com

Made in Italy



Safety rules

FOR PROFESSIONAL USE ONLY. Strictly respect the information reported on the labels and consult safety data sheets before use.

N.B.: CLOTHS AND SPONGES SOAKED OF PRODUCT MIGHT TO CATCH FIRE THROUGH AUTOCOMBUSTION. AFTER USE WET THEM WITH A LOT OF WATER, LET THEM DRYING AND DISPOSE THEM IN ACCORDANCE ODF LOCAL FORCE REGULATION.

Disposal of waste

Dispose not used product and empty containers in accordance of local in force regulations.

WARNING: The information reported in present technical data sheet are for guidance only and they do not hold our responsibility. Adapt the use of our products to the environmental conditions and materials to be treated.

REV.4 25-03-2013 Current Technical Data Sheet replaces the previous one.